

Contents

Page


Han® Q 2/0	13.02
Han® Q 2/0 High Voltage	13.04
Han® Q 5/0	13.06
Han® Q 5/0 Quick Lock	13.08
Han® Q 7/0	13.10
Han® Q 12/0	13.12
Han® Q 8/0	13.14
Han® Q 8/0 Quick Lock	13.16
Han® Q 17	13.18
Han® Q 4/2	13.20
Han® Q 4/2 Axial screw	13.22
Han® Q Data RJ45	13.24
Hoods/Housings Han-Compact®	13.26

Features

- Compact designed connector for high current ratings
- 16 coding options
- For hoods/housings size Han® 3 A
- Finger protected male and female contacts
- Assembly without special tool by axial screw termination

Attention


- By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.
- For termination please use only hexagonal screw driver with wrench size SW 2.
- If PE contact is not used:
Please screw the PE contact maximal on both sides clockwise with a hexagonal screwdriver, wrench size SW 2.



Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



- Wire gauge:
- ① 2.5 mm²
 - ② 4 mm²
 - ③ 6 mm²
 - ④ 10 mm²

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	2 + PE
Electrical data acc. to EN 61 984	40 A 400 V 6 kV 3
Rated current	40 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL/CSA	400 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
Contact resistance	≤ 1 mΩ
Axial screw termination	
- mm ²	2.5 ... 10 mm ²
- AWG	14 ... 8
Tightening torque	1.8 Nm
Stripping length	8 mm ⁺¹

Hoods/Housings	
Selection of hoods/housings	see chapter 30 / chapter 31

Plastic hoods/housings	
Material	polycarbonate
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 67
Hoods/Housings, metal	
Material	zinc die-cast
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 44 IP 67 is achieved with seal screw 09 20 000 9918

Accessories	
Cable clamps	chapter 40
Sealing screw	chapter 40



Number of contacts

2 + 



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal				
2.5 ... 6 mm ²	09 12 002 2653	09 12 002 2753		
4 ... 10 mm ²	09 12 002 2651	09 12 002 2751		
Coding element	09 12 000 9922	09 12 000 9922		

Han
Q

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2 for axial setscrew			
with grip 	09 99 000 0313		
adapter 1/4" 	09 99 000 0369		

13
03


Stock items in bold type

Features

- Compact designed connector for high current ratings with axial screw terminal
- 16 coding options
- For hoods/housings size Han® 3 A
- Finger protected male and female contacts
- For high voltages please use heat shrink tube (included in delivery range)

Attention


- By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.
- For termination please use only hexagonal screw driver with wrench size SW 2.
- If PE contact is not used:
Please screw the PE contact maximal on both sides clockwise with a hexagonal screwdriver, wrench size SW 2.



Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Wire gauge:

- ① 2.5 mm²
- ② 4 mm²
- ③ 6 mm²
- ④ 10 mm²

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	2 + PE
Electrical data acc. to EN 61 984	40 A 830 V 6 kV 3
Rated current	40 A
Rated voltage	830 V
Rated impulse voltage	6 kV
Pollution degree	3
Rated voltage acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
Contact resistance	≤ 1 mΩ
Axial screw termination	
- mm ²	2.5 ... 10 mm ²
- AWG	14 ... 8
Tightening torque	1.8 Nm
Stripping length	8 mm ⁺¹

Hoods/Housings

Selection of hoods/housings see chapter 30 / chapter 31

Plastic hoods/housings

Material	polycarbonate
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 67

Hoods/Housings, metal

Material	zinc die-cast
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 44 IP 67 is achieved with seal screw 09 20 000 9918

Accessories

Cable clamps	chapter 40
Sealing screw	chapter 40

Number of contacts

2 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal with heat shrink tube				
2.5 ... 6 mm ²	09 12 002 2654	09 12 002 2754		
4 ... 10 mm ²	09 12 002 2652	09 12 002 2752		
Coding element	09 12 000 9922	09 12 000 9922		

Han Q

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2 for axial setscrew			
with grip	09 99 000 0313		
 adapter 1/4"	09 99 000 0369		

13
05

Stock items in bold type

Features

- 5 contact chambers for crimp contacts of Han E® series
- Space-saving and compact design
- Leading protective ground with screw terminal
- Compatible with plastic and metal hoods of series Han® 3 A


Attention

By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Ambient temperature

- Wire gauge:
- ① 1.0 mm²
 - ② 1.5 mm²
 - ③ 2.5 mm²

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	5 + PE
Electrical data acc. to EN 61 984	16 A 230/400 V 4 kV 3
Rated current	16 A
Rated voltage conductor - ground	230 V
Rated voltage conductor - conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Pollution degree 2 also	16 A 320/500 V 4 kV 2
Rated voltage acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 1 mΩ
Crimp terminal	
- mm²	0.14 ... 2.5 mm²
- AWG	26 ... 14
PE screw terminal	
- mm²	2.5 mm²
- AWG	14

Hoods/Housings

Selection of hoods/housings see chapter 30 / chapter 31

Plastic hoods/housings

Material polycarbonate
Flammability acc. to UL 94 V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector IP 67

Hoods/Housings, metal

Material zinc die-cast
Degree of protection acc. to DIN EN 60 529 for coupled connector IP 44
IP 67 is achieved with seal screw 09 20 000 9918

Accessories

Crimping tools chapter 99
Cable clamps chapter 40
Sealing screw chapter 40

Number of contacts

5 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
<p>Crimp terminal</p> <p>Order crimp contacts separately</p>	09 12 005 3001	09 12 005 3101	<p>Contact arrangement view from termination side</p>	
<p>Coding pin</p>		09 33 000 9954		<p>Use of the coding pin prevents incorrect mating to other connectors of the same type. The male pin should be omitted from the opposing cavity in the male insert.</p>

Han Q

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																											
		Male contact	Female contact																													
<p>Crimp contacts</p> <p>Power contacts</p> <p>silver plated</p>	0.14-0.37	09 33 000 6127	09 33 000 6227		<p>Operating contact Identification</p> <p>Relay contact</p>																											
	0.5	09 33 000 6121	09 33 000 6220																													
	0.75	09 33 000 6114	09 33 000 6214																													
	1	09 33 000 6105	09 33 000 6205																													
	1.5	09 33 000 6104	09 33 000 6204																													
	2.5	09 33 000 6102	09 33 000 6202																													
<p>gold plated</p>	0.14-0.37	09 33 000 6117	09 33 000 6217	<table border="1"> <thead> <tr> <th>Identification</th> <th colspan="2">Wire gauge</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>no groove</td> <td>0.14-0.37 mm²</td> <td>AWG 26-22</td> <td>7.5 mm</td> </tr> <tr> <td>no groove</td> <td>0.5 mm²</td> <td>AWG 20</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove*</td> <td>0.75 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove</td> <td>1 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>2 grooves</td> <td>1.5 mm²</td> <td>AWG 16</td> <td>7.5 mm</td> </tr> <tr> <td>3 grooves</td> <td>2.5 mm²</td> <td>AWG 14</td> <td>7.5 mm</td> </tr> </tbody> </table> <p>* on the back crimp collar</p>	Identification	Wire gauge		Stripping length	no groove	0.14-0.37 mm²	AWG 26-22	7.5 mm	no groove	0.5 mm²	AWG 20	7.5 mm	1 groove*	0.75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1.5 mm²	AWG 16	7.5 mm	3 grooves	2.5 mm²	AWG 14	7.5 mm
Identification	Wire gauge		Stripping length																													
no groove	0.14-0.37 mm²	AWG 26-22	7.5 mm																													
no groove	0.5 mm²	AWG 20	7.5 mm																													
1 groove*	0.75 mm²	AWG 18	7.5 mm																													
1 groove	1 mm²	AWG 18	7.5 mm																													
2 grooves	1.5 mm²	AWG 16	7.5 mm																													
3 grooves	2.5 mm²	AWG 14	7.5 mm																													
	0.5	09 33 000 6122	09 33 000 6222																													
	0.75	09 33 000 6115	09 33 000 6215																													
	1	09 33 000 6118	09 33 000 6218																													
	1.5	09 33 000 6116	09 33 000 6216																													
	2.5	09 33 000 6123	09 33 000 6223																													
<p>Relay contact</p> <p>silver plated</p>	0.75-1	09 33 000 6109																														
	1.5	09 33 000 6110																														
	2.5	09 33 000 6111																														
<p>F.O. contacts</p> <p>for 1 mm plastic fibre</p>		20 10 001 3311	20 10 001 3321																													

Crimp contacts 0.14 ... 0.37 mm² only used with BUCHANAN crimping tool 09 99 000 0001

Stock items in bold type

Features

- Innovative Han-Quick Lock® termination technology with up to 20% reduced wiring times
- Field assembly without special tools
- Compatible with Han® Q 5/0 standard inserts
- Compatible with plastic and metal hoods of series Han® 3 A
- Vibration and shock resistant


Attention

By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.


Measuring and testing techniques according to DIN EN 60 512-5



Ambient temperature

- Wire gauge:
- ① 1.0 mm²
 - ② 1.5 mm²
 - ③ 2.5 mm²

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	5 + PE
Electrical data	
acc. to EN 61 984	16 A 230/400 V 4 kV 3
Rated current	16 A
Rated voltage conductor - ground	230 V
Rated voltage conductor - conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3
Rated voltage	
acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
Contact resistance	≤ 1 mΩ
Quick Lock termination	
- mm²	0.5 ... 2.5 mm²
- AWG	20 ... 14

Hoods/Housings	
Selection of hoods/housings	see chapter 30 / chapter 31
Plastic hoods/housings	
Material	polycarbonate
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529	
for coupled connector	IP 67
Hoods/Housings, metal	
Material	zinc die-cast
Degree of protection acc. to DIN EN 60 529	
for coupled connector	IP 44
	IP 67 is achieved with seal screw 09 20 000 9918

Accessories	
Cable clamps	chapter 40
Sealing screw	chapter 40

Han
Q

Number of contacts

5 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han-Quick Lock® 	09 12 005 2633	09 12 005 2733		

Han
Q

Features

- 7 contact chambers for crimp contacts of Han D® series
- Space-saving and compact design
- Leading protective ground with screw terminal
- Compatible with plastic and metal hoods of series Han® 3 A
- 6 different coding possibilities by means of coding pin


Attention

By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



- Wire gauge:
- ① 0.75 mm²
 - ② 1.5 mm²
 - ③ 2.5 mm²

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	7 + PE
Electrical data acc. to EN 61 984	10 A 400 V 6 kV 3
Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Pollution degree 2 also	10 A 400/690 V 6 kV 2
Rated voltage acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 3 mΩ
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14
PE screw terminal	
- mm ²	2.5 mm ²
- AWG	14

Hoods/Housings

Selection of hoods/housings see chapter 30 / chapter 31

Plastic hoods/housings

Material polycarbonate
 Flammability acc. to UL 94 V 0
 Degree of protection acc. to DIN EN 60 529 for coupled connector IP 67

Hoods/Housings, metal

Material zinc die-cast
 Degree of protection acc. to DIN EN 60 529 for coupled connector IP 44
 IP 67 is achieved with seal screw 09 20 000 9918

Accessories

Crimping tools	chapter 99
Cable clamps	chapter 40
Sealing screw	chapter 40

Number of contacts

7 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 12 007 3001	09 12 007 3101		Contact arrangement view from termination side
Coding pins 	09 12 000 9901	09 12 000 9902		

Han Q

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																																		
		Male contact	Female contact																																				
Crimp contacts Power contacts silver plated 	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6104 09 15 000 6103 09 15 000 6105 09 15 000 6102 09 15 000 6101 09 15 000 6106	09 15 000 6204 09 15 000 6203 09 15 000 6205 09 15 000 6202 09 15 000 6201 09 15 000 6206		<table border="1"> <thead> <tr> <th colspan="2">Wire gauge</th> <th>∅</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.14-0.37</td> <td>mm²</td> <td>AWG 26-22</td> <td>0.9</td> <td>8 mm</td> </tr> <tr> <td>0.5</td> <td>mm²</td> <td>AWG 20</td> <td>1.1</td> <td>8 mm</td> </tr> <tr> <td>0.75</td> <td>mm²</td> <td>AWG 18</td> <td>1.3</td> <td>8 mm</td> </tr> <tr> <td>1</td> <td>mm²</td> <td>AWG 18</td> <td>1.45</td> <td>8 mm</td> </tr> <tr> <td>1.5</td> <td>mm²</td> <td>AWG 16</td> <td>1.75</td> <td>8 mm</td> </tr> <tr> <td>2.5</td> <td>mm²</td> <td>AWG 14</td> <td>2.25</td> <td>6 mm</td> </tr> </tbody> </table>	Wire gauge		∅	Stripping length	0.14-0.37	mm²	AWG 26-22	0.9	8 mm	0.5	mm²	AWG 20	1.1	8 mm	0.75	mm²	AWG 18	1.3	8 mm	1	mm²	AWG 18	1.45	8 mm	1.5	mm²	AWG 16	1.75	8 mm	2.5	mm²	AWG 14	2.25	6 mm
Wire gauge		∅	Stripping length																																				
0.14-0.37	mm²	AWG 26-22	0.9	8 mm																																			
0.5	mm²	AWG 20	1.1	8 mm																																			
0.75	mm²	AWG 18	1.3	8 mm																																			
1	mm²	AWG 18	1.45	8 mm																																			
1.5	mm²	AWG 16	1.75	8 mm																																			
2.5	mm²	AWG 14	2.25	6 mm																																			
gold plated 	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226																																				
F.O. contacts for 1 mm plastic fibre		20 10 001 3211	20 10 001 3221																																				

13
11

Stock items in bold type

Features

- 12 contact chambers taking the control contacts of the series Han D® with crimp termination
- 1 PE contact with innovative Han-Quick Lock® termination technology
- 2 coding pins offering 16 coding possibilities
- Inserts suitable for metal and plastic hoods and housings of the series Han® 3 A


Attention

By using in Han® 3 A HPR hoods/housings the sealing on the insert has to be removed.

Current carrying capacity


The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



- Wire gauge:
- ① 0.75 mm²
 - ② 1.5 mm²
 - ③ 2.5 mm²

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	12 + PE
Electrical data acc. to EN 61 984	10 A 400 V 6 kV 3
Rated current	10 A
Rated voltage	400 V
Rated impulse voltage	6 kV
Pollution degree	3
Pollution degree 2 also	10 A 400/690 V 6 kV 2
Rated voltage acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500


Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 3 mΩ
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14
PE contact	Quick Lock termination
- mm ²	0.5 ... 2.5 mm ²
- AWG	20 ... 14

Hoods/Housings	
Selection of hoods/housings	see chapter 30 / chapter 31
Plastic hoods/housings	
Material	polycarbonate
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 67
Hoods/Housings, metal	
Material	zinc die-cast
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 44 IP 67 is achieved with seal screw 09 20 000 9918

Accessories	
Crimping tools	chapter 99
Cable clamps	chapter 40
Sealing screw	chapter 40

Number of contacts

12 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
<p>Crimp termination/ Han-Quick Lock® Order crimp contacts separately</p> <p>PE contact: Quick Lock termination</p>	09 12 012 3001	09 12 012 3101		
<p>Coding pins</p>	09 12 000 9924	09 12 000 9924		<p>Range of delivery: 20 pieces per frame</p>

Han Q

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																																			
		Male contact	Female contact																																					
<p>Crimp contacts</p> <p>Power contacts</p> <p>silver plated</p> <p>gold plated</p>	<p>0.14-0.37</p> <p>0.5</p> <p>0.75</p> <p>1</p> <p>1.5</p> <p>2.5</p> <p>0.14-0.37</p> <p>0.5</p> <p>0.75</p> <p>1</p> <p>1.5</p> <p>2.5</p>	<p>09 15 000 6104</p> <p>09 15 000 6103</p> <p>09 15 000 6105</p> <p>09 15 000 6102</p> <p>09 15 000 6101</p> <p>09 15 000 6106</p> <p>09 15 000 6124</p> <p>09 15 000 6123</p> <p>09 15 000 6125</p> <p>09 15 000 6122</p> <p>09 15 000 6121</p> <p>09 15 000 6126</p>	<p>09 15 000 6204</p> <p>09 15 000 6203</p> <p>09 15 000 6205</p> <p>09 15 000 6202</p> <p>09 15 000 6201</p> <p>09 15 000 6206</p> <p>09 15 000 6224</p> <p>09 15 000 6223</p> <p>09 15 000 6225</p> <p>09 15 000 6222</p> <p>09 15 000 6221</p> <p>09 15 000 6226</p>	<table border="1"> <thead> <tr> <th colspan="3">Wire gauge</th> <th>∅</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.14-0.37</td> <td>mm²</td> <td>AWG 26-22</td> <td>0.9</td> <td>8 mm</td> </tr> <tr> <td>0.5</td> <td>mm²</td> <td>AWG 20</td> <td>1.1</td> <td>8 mm</td> </tr> <tr> <td>0.75</td> <td>mm²</td> <td>AWG 18</td> <td>1.3</td> <td>8 mm</td> </tr> <tr> <td>1</td> <td>mm²</td> <td>AWG 18</td> <td>1.45</td> <td>8 mm</td> </tr> <tr> <td>1.5</td> <td>mm²</td> <td>AWG 16</td> <td>1.75</td> <td>8 mm</td> </tr> <tr> <td>2.5</td> <td>mm²</td> <td>AWG 14</td> <td>2.25</td> <td>6 mm</td> </tr> </tbody> </table>	Wire gauge			∅	Stripping length	0.14-0.37	mm²	AWG 26-22	0.9	8 mm	0.5	mm²	AWG 20	1.1	8 mm	0.75	mm²	AWG 18	1.3	8 mm	1	mm²	AWG 18	1.45	8 mm	1.5	mm²	AWG 16	1.75	8 mm	2.5	mm²	AWG 14	2.25	6 mm	
Wire gauge			∅	Stripping length																																				
0.14-0.37	mm²	AWG 26-22	0.9	8 mm																																				
0.5	mm²	AWG 20	1.1	8 mm																																				
0.75	mm²	AWG 18	1.3	8 mm																																				
1	mm²	AWG 18	1.45	8 mm																																				
1.5	mm²	AWG 16	1.75	8 mm																																				
2.5	mm²	AWG 14	2.25	6 mm																																				
<p>F.O. contacts</p> <p>for 1 mm plastic fibre</p>		20 10 001 3211	20 10 001 3221																																					

13
13

Stock items in bold type

Features


- 8 contact chambers for crimp contacts of Han E® series
- Space-saving and compact design
- Leading protective ground with crimp terminal
- Inserts suitable for metal and plastic hoods and housings of Han-Compact® series
- ISO 23 570 / DESINA conform product



Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Ambient temperature

Wire gauge: ① 1.5 mm²
② 2.5 mm²

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
Approvals	
Inserts	
Number of contacts	8 + PE
Electrical data acc. to EN 61 984	
Mounted plastic hood	16 A 500 V 6 kV 3
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Pollution degree 2 also	16 A 400/690 V 6 kV 2
Mounted metal hood	16 A 230/400 V 4 kV 3
Rated voltage acc. to UL/CSA	600 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500


Contacts	
Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 1 mΩ
Crimp terminal	
- mm²	0.14 ... 4 mm² partly loaded up to 4 mm² is possible
- AWG	26 ... 12

Hoods/Housings	
Plastic hoods/housings	
Material	thermoplastic
Locking element	Polyamide
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65
Hoods/Housings, metal	
Material	metal
Locking element	Stainless steel
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Accessories	
Crimping tools	chapter 99

Number of contacts

8 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 12 008 3001	09 12 008 3101		
Coding pin 		09 33 000 9954		Use of the coding pin prevents incorrect mating to other connectors of the same type. The male pin should be omitted from the opposing cavity in the male insert.

Han Q

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																																
		Male contact	Female contact																																		
Crimp contacts Power contacts silver plated 	0.14-0.37	09 33 000 6127	09 33 000 6227		<table border="1"> <thead> <tr> <th>Identification</th> <th colspan="2">Wire gauge</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>no groove</td> <td>0.14-0.37 mm²</td> <td>AWG 26-22</td> <td>7.5 mm</td> </tr> <tr> <td>no groove</td> <td>0.5 mm²</td> <td>AWG 20</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove*</td> <td>0.75 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>1 groove</td> <td>1 mm²</td> <td>AWG 18</td> <td>7.5 mm</td> </tr> <tr> <td>2 grooves</td> <td>1.5 mm²</td> <td>AWG 16</td> <td>7.5 mm</td> </tr> <tr> <td>3 grooves</td> <td>2.5 mm²</td> <td>AWG 14</td> <td>7.5 mm</td> </tr> <tr> <td>no groove</td> <td>4 mm²</td> <td>AWG 12</td> <td>7.5 mm</td> </tr> </tbody> </table>	Identification	Wire gauge		Stripping length	no groove	0.14-0.37 mm²	AWG 26-22	7.5 mm	no groove	0.5 mm²	AWG 20	7.5 mm	1 groove*	0.75 mm²	AWG 18	7.5 mm	1 groove	1 mm²	AWG 18	7.5 mm	2 grooves	1.5 mm²	AWG 16	7.5 mm	3 grooves	2.5 mm²	AWG 14	7.5 mm	no groove	4 mm²	AWG 12	7.5 mm
Identification	Wire gauge		Stripping length																																		
no groove	0.14-0.37 mm²	AWG 26-22	7.5 mm																																		
no groove	0.5 mm²	AWG 20	7.5 mm																																		
1 groove*	0.75 mm²	AWG 18	7.5 mm																																		
1 groove	1 mm²	AWG 18	7.5 mm																																		
2 grooves	1.5 mm²	AWG 16	7.5 mm																																		
3 grooves	2.5 mm²	AWG 14	7.5 mm																																		
no groove	4 mm²	AWG 12	7.5 mm																																		
gold plated 	0.14-0.37	09 33 000 6117	09 33 000 6217																																		
Relay contact silver plated 	0.75-1	09 33 000 6109	09 33 000 6209																																		
	1.5	09 33 000 6110	09 33 000 6210																																		
	2.5	09 33 000 6111	09 33 000 6211																																		
F.O. contacts for 1 mm plastic fibre		20 10 001 3311	20 10 001 3321																																		

Crimp contacts 0.14 ... 0.37 mm² only used with BUCHANAN crimping tool 09 99 000 0001

Stock items in bold type


Features

- Innovative Han-Quick Lock® termination
- Reduced wiring times; field assembly without special tools
- Compatible to Han® Q 8/0 inserts with crimp terminal
- Insert suitable for standard plastic hoods/housings and metal hoods/housings with additional PE contact of the size Han-Compact®
- Leading protective ground contact

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Ambient temperature

- Wire gauge:
- ① 0.5 mm²
 - ② 1.5 mm²
 - ③ 2.5 mm²

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Inserts

Number of contacts	8 + PE
Electrical data acc. to EN 61 984	16 A 500 V 6 kV 3
Rated current	16 A
Rated voltage	500 V
Rated impulse voltage	6 kV
Pollution degree	3
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 µm Ag
Contact resistance	≤ 3 mΩ
Quick Lock termination	
- mm ²	0.5 ... 2.5 mm ²
- AWG	20 ... 14
Max. insulation diameter	3.6 mm

Hoods/Housings

Selection of hoods/housings see chapter 30 / chapter 31

Plastic hoods/housings

Material	polycarbonate
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 67


Hoods/Housings, metal, with additional PE contact

Material	zinc die-cast
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 44
	IP 67 is achieved with seal screw 09 20 000 9918

Han Q

Number of contacts

8 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Han-Quick Lock® 	09 12 008 2633	09 12 008 2733		

Han
Q


Features

- 17 contact chambers for crimp contacts of Han D® series
- Space-saving and compact design
- Leading protective ground with crimp terminal
- Inserts suitable for metal and plastic hoods and housings of Han-Compact® series
- 3 coding possibilities by using a coding pin instead of fixing screw

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Wire gauge:

- ① 0.5 mm²
- ② 1.0 mm²
- ③ 1.5 mm²

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	17 + PE
Electrical data acc. to EN 61 984	10 A 250 V 4 kV 2
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	2
Rated voltage acc. to UL/CSA	250 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 3 mΩ
Crimp terminal	
- mm ²	0.14 ... 2.5 mm ²
- AWG	26 ... 14

Hoods/Housings


Plastic hoods/housings	
Material	thermoplastic
Locking element	Polyamide
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65
Hoods/Housings, metal	
Material	metal
Locking element	Stainless steel
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Accessories

Crimping tools chapter 99

Number of contacts

17 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 12 017 3001	09 12 017 3101	<p>Contact arrangement view from termination side</p>	

Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm																																			
		Male contact	Female contact																																					
Crimp contacts Power contacts silver plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6104 09 15 000 6103 09 15 000 6105 09 15 000 6102 09 15 000 6101 09 15 000 6106	09 15 000 6204 09 15 000 6203 09 15 000 6205 09 15 000 6202 09 15 000 6201 09 15 000 6206																																					
gold plated	0.14-0.37 0.5 0.75 1 1.5 2.5	09 15 000 6124 09 15 000 6123 09 15 000 6125 09 15 000 6122 09 15 000 6121 09 15 000 6126	09 15 000 6224 09 15 000 6223 09 15 000 6225 09 15 000 6222 09 15 000 6221 09 15 000 6226	<table border="1"> <thead> <tr> <th colspan="3">Wire gauge</th> <th>∅</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.14-0.37</td> <td>mm²</td> <td>AWG 26-22</td> <td>0.9</td> <td>8 mm</td> </tr> <tr> <td>0.5</td> <td>mm²</td> <td>AWG 20</td> <td>1.1</td> <td>8 mm</td> </tr> <tr> <td>0.75</td> <td>mm²</td> <td>AWG 18</td> <td>1.3</td> <td>8 mm</td> </tr> <tr> <td>1</td> <td>mm²</td> <td>AWG 18</td> <td>1.45</td> <td>8 mm</td> </tr> <tr> <td>1.5</td> <td>mm²</td> <td>AWG 16</td> <td>1.75</td> <td>8 mm</td> </tr> <tr> <td>2.5</td> <td>mm²</td> <td>AWG 14</td> <td>2.25</td> <td>6 mm</td> </tr> </tbody> </table>	Wire gauge			∅	Stripping length	0.14-0.37	mm²	AWG 26-22	0.9	8 mm	0.5	mm²	AWG 20	1.1	8 mm	0.75	mm²	AWG 18	1.3	8 mm	1	mm²	AWG 18	1.45	8 mm	1.5	mm²	AWG 16	1.75	8 mm	2.5	mm²	AWG 14	2.25	6 mm	
Wire gauge			∅	Stripping length																																				
0.14-0.37	mm²	AWG 26-22	0.9	8 mm																																				
0.5	mm²	AWG 20	1.1	8 mm																																				
0.75	mm²	AWG 18	1.3	8 mm																																				
1	mm²	AWG 18	1.45	8 mm																																				
1.5	mm²	AWG 16	1.75	8 mm																																				
2.5	mm²	AWG 14	2.25	6 mm																																				
F.O. contacts for 1 mm plastic fibre		20 10 001 3211	20 10 001 3221																																					

Stock items in bold type


Features

- 4 power contacts Han® C and 2 signal contacts Han D®
- Finger protection
- Leading protective ground with crimp terminal
- Inserts suitable for standard plastic and metal hoods/housings with additional PE contact from the Han-Compact® size
- 3 coding possibilities by using a coding pin instead of fixing screw

Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Wire gauge:

① 2.5 mm²

② 4 mm²

Technical characteristics

Specifications DIN EN 60 664-1
DIN EN 61 984

Approvals

Inserts

Number of contacts	4 / 2 + PE
Electrical data acc. to EN 61 984	
<u>Power side</u>	40 A 400/690 V 6 kV 3
Rated current	40 A
Rated voltage conductor - ground	400 V
Rated voltage conductor - conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	3
<u>Signal side</u>	10 A 250 V 4 kV 3
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3

Rated voltage acc. to UL/CSA	600 / 250 V
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
- hard-gold plated	2 μm Au over 3 μm Ni
Contact resistance	≤ 0.3 mΩ
Crimp terminal	
- mm ²	1.5 ... 6 mm ² / 0.14 ... 2.5 mm ²
- AWG	16 ... 10 / 26 ... 14
Max. insulation diameter - Power contacts	5 mm

Hoods/Housings


Plastic hoods/housings	
Material	thermoplastic
Locking element	Polyamide
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Accessories

Crimping tools	chapter 99
----------------	------------

Number of contacts

4/2 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Crimp terminal Order crimp contacts separately	09 12 006 3041	09 12 006 3141	<p>Contact arrangement view from termination side</p>	

Han Q

Identification	Wire gauge (mm ²)	Part number		Drawing	Dimensions in mm																									
		Male contact	Female contact																											
Crimp contacts Han® C contacts silver plated	1.5 2.5 4 6	09 32 000 6104 09 32 000 6105 09 32 000 6107 09 32 000 6108	09 32 000 6204 09 32 000 6205 09 32 000 6207 09 32 000 6208		<table border="1"> <thead> <tr> <th colspan="2">Wire gauge</th> <th>∅</th> <th colspan="2">Stripping length</th> </tr> </thead> <tbody> <tr> <td>1.5</td> <td>mm²</td> <td>AWG 16</td> <td>1.75</td> <td>9 mm</td> </tr> <tr> <td>2.5</td> <td>mm²</td> <td>AWG 14</td> <td>2.25</td> <td>9 mm</td> </tr> <tr> <td>4</td> <td>mm²</td> <td>AWG 12</td> <td>2.85</td> <td>9.6 mm</td> </tr> <tr> <td>6</td> <td>mm²</td> <td>AWG 10</td> <td>3.5</td> <td>9.6 mm</td> </tr> </tbody> </table>	Wire gauge		∅	Stripping length		1.5	mm ²	AWG 16	1.75	9 mm	2.5	mm ²	AWG 14	2.25	9 mm	4	mm ²	AWG 12	2.85	9.6 mm	6	mm ²	AWG 10	3.5	9.6 mm
Wire gauge		∅	Stripping length																											
1.5	mm ²	AWG 16	1.75	9 mm																										
2.5	mm ²	AWG 14	2.25	9 mm																										
4	mm ²	AWG 12	2.85	9.6 mm																										
6	mm ²	AWG 10	3.5	9.6 mm																										

13
21


Stock items in bold type

Features

- Field assembly without special tools - reduced wiring times
- Compatible with Han® Q 4/2 standard inserts with crimp terminations
- Space-saving and compact design
- Inserts suitable for standard plastic and metal hoods/housings with additional PE contact from the Han-Compact® size
- With or without Han-Quick Lock® signal contacts as an option

Attention


- For termination please use only hexagonal screw driver with wrench size SW 2.
- If PE contact is not used:
Please screw the PE contact maximal on both sides clockwise with a hexagonal screwdriver, wrench size SW 2.



Current carrying capacity

The current carrying capacity of the connectors is limited by the thermal load capability of the contact element material including the connections and the insulating parts. The derating curve is therefore valid for currents which flow constantly (non-intermittent) through each contact element of the connector evenly, without exceeding the allowed maximum temperature.

Measuring and testing techniques according to DIN EN 60 512-5



Wire gauge: ① 4 mm²
 ② 6 mm²

Technical characteristics

Specifications DIN EN 60 664-1
 DIN EN 61 984

Inserts

Number of contacts	4 / 2 + PE
Electrical data acc. to EN 61 984	
<u>Power side</u>	40 A 400/690 V 6 kV 3
Rated current	40 A
Rated voltage conductor - ground	400 V
Rated voltage conductor - conductor	690 V
Rated impulse voltage	6 kV
Pollution degree	3
<u>Signal side</u>	10 A 250 V 4 kV 3
Rated current	10 A
Rated voltage	250 V
Rated impulse voltage	4 kV
Pollution degree	3
Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Mechanical working life - mating cycles	≥ 500

Contacts

Material	copper alloy
Surface	
- hard-silver plated	3 μm Ag
<u>Power contacts</u>	
Contact resistance	≤ 0.3 mΩ
Axial screw termination	
- mm ²	4 ... 10 mm ²
- AWG	12 ... 8
Max. insulation diameter	7.3 mm
Stripping length	8 mm
Tightening torque	1.8 Nm
<u>Signal contacts</u>	
Contact resistance	≤ 3 mΩ
Han-Quick Lock®	
- mm ²	0.25 ... 1.5 mm ²
- AWG	23 ... 16
Max. insulation diameter	3 mm
Stripping length	10 mm

Hoods/Housings

Plastic hoods/housings	
Material	thermoplastic
Locking element	Polyamide
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Han
Q

Number of contacts

4/2 +



Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
Axial screw terminal				
with Han-Quick Lock® signal contacts 	09 12 006 2663	09 12 006 2763		
without Han-Quick Lock® signal contacts	09 12 006 2666	09 12 006 2766		

Han Q

Identification	Part number	Drawing	Dimensions in mm
Hex key SW 2 for axial setscrew			
with grip 	09 99 000 0313		
adapter 1/4" 	09 99 000 0369		

Stock items in bold type

Features

- Combination connector / Ethernet connector based on RJ45 / additionally maximum 10 signal D-Sub contacts, crimp terminal
- Compact design
- High contact density
- Turned D-Sub contacts of performance level 1*
- Suitable for hoods and housings of series Han-Compact®

Technical characteristics

Specifications	DIN EN 60 664-1 DIN EN 61 984
----------------	----------------------------------

Inserts

Ethernet connector

Terminal	RJ45 acc. to IEC 60 603-7
Wire gauge	- flexible
Transmission features	Cat. 5e
Number of contacts	8

Signal side

Number of contacts	10
Electrical data	
acc. to EN 61 984	5 A 50 V 0.8 kV 3
Rated current	5 A
Rated voltage	50 V
Rated impulse voltage	0.8 kV
Pollution degree	3

Insulation resistance	≥ 10 ¹⁰ Ω
Material	polycarbonate
Limiting temperatures	-40 °C ... 85 °C
Flammability acc. to UL 94	V 0
Mechanical working life	
- mating cycles	≥ 500

Contacts

Crimp terminal	
- mm ²	0.13 ... 0.52 mm ²
- AWG	26 ... 20
turned contacts	Performance level 1 as per CECC 75 301-802, 500 mating cycles, 10 days 4 mixed gas test - IEC 60 512

Hoods/Housings

Plastic hoods/housings


Material	thermoplastic
Locking element	Polyamide
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Flammability acc. to UL 94	V 0
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Hoods/Housings, metal

Material	metal
Locking element	Stainless steel
Hoods/Housings seal	NBR
Limiting temperatures	-40 °C ... 125 °C
Degree of protection acc. to DIN EN 60 529 for coupled connector	IP 65

Number of contacts

8













Identification	Part number		Drawing	Dimensions in mm
	Male insert (M)	Female insert (F)		
<p>Han® Q Data RJ45 Order crimp contacts separately female insert usable for panel feed through for patch cables</p>	09 12 011 3001	09 12 011 3111		

Han Q



Identification	Wire gauge (mm²)	Part number		Drawing	Dimensions in mm												
		Male contact	Female contact														
<p>Individual contacts Han® D-Sub contacts gold plated</p>	0.13-0.33 0.33-0.52	61 03 000 0094 61 03 000 0073	61 03 000 0096 61 03 000 0074	<table border="1"> <thead> <tr> <th colspan="2">Wire gauge</th> <th>∅</th> <th>Stripping length</th> </tr> </thead> <tbody> <tr> <td>0.13-0.33 mm²</td> <td>AWG 26-22</td> <td>0.9</td> <td>5 mm</td> </tr> <tr> <td>0.33-0.52 mm²</td> <td>AWG 22-20</td> <td>1.12</td> <td>5 mm</td> </tr> </tbody> </table>	Wire gauge		∅	Stripping length	0.13-0.33 mm²	AWG 26-22	0.9	5 mm	0.33-0.52 mm²	AWG 22-20	1.12	5 mm	
Wire gauge		∅	Stripping length														
0.13-0.33 mm²	AWG 26-22	0.9	5 mm														
0.33-0.52 mm²	AWG 22-20	1.12	5 mm														
<p>RJ45 plug AMP (for replacement)</p> <p>AWG 24 ... 26 ∅ 0.89 mm ... 0.99 mm</p>		09 12 000 9958															

13
25

Metal

Identification	Part number	Drawing	Dimensions in mm
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for Han-Compact® half gland with separate PE termination for all inserts of size Han-Compact® 	<p>black powder coated 19 12 708 0511</p> <p>black chromated 19 12 008 0511</p>	<p>M25</p> <p>M25</p> 	<p>70,9</p> <p>49,9</p> <p>29</p> <p>35</p>
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for Han-Compact® half gland for Han® Q 8/0 Crimp, Han® Q 17/0 and Han® Q Data RJ45 	<p>black powder coated 19 12 708 0501</p> <p>black chromated 19 12 008 0501</p>	<p>M25</p> <p>M25</p> 	<p>59,5</p> <p>49,9</p> <p>15,7</p> <p>29</p> <p>35</p>
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for standard cable glands with separate PE termination for all inserts of size Han-Compact® 	<p>black powder coated 19 12 008 0526</p>	<p>M25</p> 	<p>73</p> <p>65,7</p> <p>5</p> <p>29</p> <p>35</p>
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for Han-Compact® half gland with separate PE termination for all inserts of size Han-Compact® 	<p>black powder coated 19 12 708 0411</p> <p>black chromated 19 12 008 0411</p>	<p>M25</p> <p>M25</p> 	<p>88,9</p> <p>49,9</p> <p>29</p> <p>35</p>
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for standard cable glands with separate PE termination for all inserts of size Han-Compact® 	<p>black powder coated 19 12 008 0426</p>	<p>M25</p> 	<p>73</p> <p>50</p> <p>65,7</p> <p>29</p> <p>35</p>

Metal

Identification	Part number		Drawing	Dimensions in mm
<p>Housings, bulkhead mounting</p> 	<p>black powder coated 09 12 708 0301</p> <p>black chromated 09 12 008 0301</p>			






Han
Q

Thermoplastic

Identification	Part number		Drawing	Dimensions in mm
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for Han-Compact® half gland 	<p>09 12 008 0527</p>	<p>Pg 16</p>		
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for Han-Compact® half gland 	<p>19 12 008 0429 09 12 008 0427 09 12 008 0429</p>	<p>M25 Pg 16 Pg 21</p>		
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for flexible conduits Adaptaflex PAFS18 	<p>09 12 008 0428</p>	<p>PAFS 18</p>		

Han
Q

Thermoplastic

Identification	Part number		Drawing	Dimensions in mm
Housings, bulkhead mounting straight 	09 12 008 0327	-		
Housings, bulkhead mounting angled 	09 12 008 0902	-		
Housings, surface mounting • for Han-Compact® half gland 	09 12 008 0901	Pg 16		
Hoods, cable to cable • for Han-Compact® half gland 	19 12 008 0729 09 12 008 0727	M25 Pg 16		
Hoods, cable to cable • for flexible conduits Adaptaflex PAFS18 	09 12 008 0728	PAFS 18		




Han Q

Metal nickel-plated for EMC applications

Identification	Part number		Drawing	Dimensions in mm
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for Han-Compact® EMC half gland with separate PE termination for all inserts of size Han-Compact® 	19 12 008 0512	M25		
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for Han-Compact® EMC half gland for Han® Q 8/0 Crimp, Han® Q 17/0 and Han® Q Data RJ45 	19 12 008 0502	M25		
<p>Hoods</p> <ul style="list-style-type: none"> side-entry for standard EMC cable glands with separate PE termination for all inserts of size Han-Compact® 	19 12 008 0528	M25		
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for Han-Compact® EMC half gland with separate PE termination for all inserts of size Han-Compact® 	19 12 008 0412	M25		
<p>Hoods</p> <ul style="list-style-type: none"> top-entry for standard EMC cable glands with separate PE termination for all inserts of size Han-Compact® 	19 12 008 0428	M25		









Han Q

Metal nickel-plated for EMC applications

Identification	Part number		Drawing	Dimensions in mm
<p>Housings, bulkhead mounting</p> 	<p>09 12 008 0303</p>			









Han
Q

Accessories

Identification	Part number	Drawing	Dimensions in mm																																
<p>Han-Compact® half gland</p> <ul style="list-style-type: none"> • Metal • for hoods 	<p>19 12 000 5057 19 12 000 5058</p>	<p>M25 M25</p> 	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">cable</th> <th rowspan="2">SW</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>19 12 000 5057</td> <td>10,5 mm</td> <td>14 mm</td> <td>28</td> </tr> <tr> <td>19 12 000 5058</td> <td>14 mm</td> <td>17 mm</td> <td>28</td> </tr> </tbody> </table>		cable		SW	min.	max.	19 12 000 5057	10,5 mm	14 mm	28	19 12 000 5058	14 mm	17 mm	28																		
	cable		SW																																
	min.	max.																																	
19 12 000 5057	10,5 mm	14 mm	28																																
19 12 000 5058	14 mm	17 mm	28																																
<p>Han-Compact® half gland</p> <ul style="list-style-type: none"> • Thermoplastic • for hoods 	<p>19 12 000 5157 19 12 000 5158 09 00 000 5059 09 00 000 5157 09 00 000 5158</p>	<p>M25 M25 Pg 16 Pg 21 Pg 21</p> 	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">cable</th> <th rowspan="2">SW</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>19 12 000 5157</td> <td>10,5 mm</td> <td>14 mm</td> <td>30</td> </tr> <tr> <td>19 12 000 5158</td> <td>14 mm</td> <td>17 mm</td> <td>30</td> </tr> <tr> <td>09 00 000 5059</td> <td>11,5 mm</td> <td>15,5 mm</td> <td>27</td> </tr> <tr> <td>09 00 000 5157</td> <td>14 mm</td> <td>18 mm</td> <td>33</td> </tr> <tr> <td>09 00 000 5158</td> <td>17 mm</td> <td>20,5 mm</td> <td>33</td> </tr> </tbody> </table>		cable		SW	min.	max.	19 12 000 5157	10,5 mm	14 mm	30	19 12 000 5158	14 mm	17 mm	30	09 00 000 5059	11,5 mm	15,5 mm	27	09 00 000 5157	14 mm	18 mm	33	09 00 000 5158	17 mm	20,5 mm	33						
	cable		SW																																
	min.	max.																																	
19 12 000 5157	10,5 mm	14 mm	30																																
19 12 000 5158	14 mm	17 mm	30																																
09 00 000 5059	11,5 mm	15,5 mm	27																																
09 00 000 5157	14 mm	18 mm	33																																
09 00 000 5158	17 mm	20,5 mm	33																																
<p>Han-Compact® half gland</p> <ul style="list-style-type: none"> • Thermoplastic • for housings 	<p>09 00 000 5058 09 00 000 5057</p>	<p>Pg 16 Pg 16</p> 	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">cable</th> <th rowspan="2">SW</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>09 00 000 5058</td> <td>11,5 mm</td> <td>15,5 mm</td> <td>27</td> </tr> <tr> <td>09 00 000 5057</td> <td>6,5 mm</td> <td>9,5 mm</td> <td>27</td> </tr> </tbody> </table>		cable		SW	min.	max.	09 00 000 5058	11,5 mm	15,5 mm	27	09 00 000 5057	6,5 mm	9,5 mm	27																		
	cable		SW																																
	min.	max.																																	
09 00 000 5058	11,5 mm	15,5 mm	27																																
09 00 000 5057	6,5 mm	9,5 mm	27																																
<p>Han-Compact® EMC half gland</p> <ul style="list-style-type: none"> • Metal • for hoods 	<p>19 62 000 5056 19 62 000 5057 19 62 000 5058</p>	<p>M25 M25 M25</p> 	<table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">cable</th> <th rowspan="2">SW</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>19 62 000 5056</td> <td>10,5 mm</td> <td>14 mm</td> <td>28</td> </tr> <tr> <td>19 62 000 5057</td> <td>10,5 mm</td> <td>14 mm</td> <td>28</td> </tr> <tr> <td>19 62 000 5058</td> <td>14 mm</td> <td>17 mm</td> <td>28</td> </tr> </tbody> </table> <table border="1"> <thead> <tr> <th rowspan="2"></th> <th colspan="2">shielding</th> </tr> <tr> <th>min.</th> <th>max.</th> </tr> </thead> <tbody> <tr> <td>19 62 000 5056</td> <td>9 mm</td> <td>13 mm</td> </tr> <tr> <td>19 62 000 5057</td> <td>6 mm</td> <td>11 mm</td> </tr> <tr> <td>19 62 000 5058</td> <td>9 mm</td> <td>13 mm</td> </tr> </tbody> </table>		cable		SW	min.	max.	19 62 000 5056	10,5 mm	14 mm	28	19 62 000 5057	10,5 mm	14 mm	28	19 62 000 5058	14 mm	17 mm	28		shielding		min.	max.	19 62 000 5056	9 mm	13 mm	19 62 000 5057	6 mm	11 mm	19 62 000 5058	9 mm	13 mm
	cable		SW																																
	min.	max.																																	
19 62 000 5056	10,5 mm	14 mm	28																																
19 62 000 5057	10,5 mm	14 mm	28																																
19 62 000 5058	14 mm	17 mm	28																																
	shielding																																		
	min.	max.																																	
19 62 000 5056	9 mm	13 mm																																	
19 62 000 5057	6 mm	11 mm																																	
19 62 000 5058	9 mm	13 mm																																	

Stock items in bold type

Accessories

Identification	Part number		Drawing	Dimensions in mm
<p>Protection covers</p> <ul style="list-style-type: none"> • Thermoplastic • for housings for mounted male insert 	 <p>09 12 008 5407</p>			
<p>Protection covers</p> <ul style="list-style-type: none"> • Thermoplastic • for housings for mounted female insert 	 <p>09 12 008 5408</p>			
<p>Gasket for plastic housings, bulkhead mounting, straight</p>	 <p>09 12 000 9912</p>			
<p>Gasket for plastic housings, bulkhead mounting, angled, and for housings, surface mounting</p>	 <p>09 12 000 9911</p>			

Han
Q



ET 200pro distributed I/O system with degree of protection IP 65 / IP 67
Siemens AG, Erlangen, Germany

Han
Q